

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior claims listings in this application.

Listing of claims:

1. (Currently amended) A selection manifold for use with a beverage dispenser comprising:
 - a) a manifold block containing one or more cells, each of the one or more cells having an outlet opening on a face thereof and at least first and second inlet openings on the face wherein the first and second inlet openings reside on either side of the outlet opening;
 - b) a selector mechanism associated with each of the one or more cells, the selector mechanism being actionable between
 - i) a first position in which a fluid entering the cell from in the first inlet opening can pass to the outlet opening and a fluid from in the second inlet is prevented from entering the cell, and
 - ii) a second position in which the fluid entering the cell from the second inlet opening can pass to the outlet opening and the fluid from the first inlet opening is prevented from entering the cell; and
 - c) a lock to prevent unintentional change of the selector mechanism between the first and second positions.
2. (Original) The selection manifold of claim 1 wherein the manifold block comprises at least two cells.
3. (Previously Presented) The selection manifold of claim 2 wherein the first inlet opening for each of the one or more cells is supplied by a first manifold block inlet and the second inlet opening for each of the one or more cells is supplied by a second manifold block inlet opening.
4. (Currently amended) A selection manifold for use with a beverage dispenser comprising:

a) a manifold block containing one or more cells, each of the one or more cells having an outlet opening and at least first and second inlet openings on an outer surface thereof and opening into an inner surface thereof; and

b) a selector mechanism associated with each of the one or more cells, wherein the selector mechanism comprises a cap with a channel along a face thereof, and wherein the selector mechanism is configured to be actionable between

i) a first position of the face against the outer surface of the manifold block in which a fluid entering the cell from in the first inlet opening can pass to the outlet opening and a fluid from in the second inlet is prevented from entering the cell, and

ii) a second position of the face against the outer surface of the manifold block in which the fluid entering the cell from in the second inlet opening can pass to the outlet opening and the fluid from in the first inlet opening is prevented from entering the cell.

5. (Original) The selection manifold of claim 4 wherein the first and second inlet openings reside on either side of the outlet opening.

6. (Currently amended) The selection manifold of claim 5 wherein the channel provides a fluid conduit through which the fluid in the first or second inlet openings enters the block though an one of the first or second inlet opening openings adjacent to the outlet opening.

7.-19. (Cancelled)

20. (Previously presented) A beverage selection manifold comprising:

a) a cell within a manifold body, the cell including an outlet opening and first and second inlet openings; and

b) a cap configured to be removed and including a channel therein and having a face positionable against an outer wall of the cell in a first cap position and a second cap position,

wherein the channel allows fluid communication between the outlet opening and the first inlet opening in the first position and between the outlet opening

and the second inlet opening in the second position by directing the fluid from the manifold body through the channel in the removable cap and back into the manifold body.

21. (Original) The beverage selection manifold of claim 20 further comprising an attachment device configured to hold the cap against the manifold body.

22. (Original) The beverage selection manifold of claim 20 wherein
a) in the first cap position, a fluid enters the manifold body from the first inlet opening and passes to the outlet opening through the channel of the removable cap and a fluid from the second inlet opening is prevented from entering the cell, and

b) in the second cap position, a fluid enters the cell from the second inlet opening and passes to the outlet opening through the channel of the removable cap and a fluid from the first inlet opening is prevented from entering the cell.

23. (Cancelled)

24. (Currently amended) A method of switching a supply line to a dispensing valve comprising a user selecting the a fluid supply to a beverage valve from a manifold body having an inner wall opposite an outer wall, the selecting method comprising positioning a cap against the outer wall in a first position in which a first side of the cap closes a first fluid supply line located in the inner wall of the manifold body, while allowing a fluid to flow from a second fluid supply line located in the inner wall of the manifold body through the cap and into a fluid outlet line in the inner wall of the manifold body, wherein the fluid outlet line is coupled to the dispensing valve, and a second position in which a second side of the cap closes the second fluid supply line, while allowing a fluid to flow from the first fluid supply line through the cap and into the fluid outlet line.

25.-27. (Cancelled)

28. (Previously presented) A beverage selection manifold comprising:

a) a manifold body;

b) a plurality of sections within the manifold body, each section including first and second outlet orifices and first and second inlet orifices; and
c) a plurality of caps each configured to be removed from the manifold body and each including a channel therein configured to be positioned adjacent to an outer wall of one of the sections in a first cap position and a second cap position, wherein the channel provides a fluid outlet for the first outlet orifice in the first position and a fluid outlet for the second outlet orifice in the second position.

29. (Original) The beverage selection manifold of claim 28 further comprising an attachment device configured to hold the cap against the manifold body.

30. (Original) The beverage selection manifold of claim 28 wherein the carbonated water flows through the removable cap in the first position and non-carbonated water flows through the removable cap in the second position.

31. (Original) The beverage selection manifold of claim 28 wherein the beverage selection manifold is integrated into the mounting block for a mixing and dispensing valve.

32. (Previously presented) A beverage selection manifold for controlling fluid flow therein of carbonated and non-carbonated water for mixing with a syrup to form a beverage, the manifold comprising:

a) a rectangular manifold body including multiple cells, each cell having first and second inlet orifices and first and second outlet orifices, wherein the first and second inlet orifices are connected to respective first and second elongated channels positioned in the rectangular manifold body; and
b) at least one body configured to be detached from the manifold body, wherein the body is further configured to stop fluid flow from a first outlet orifice in a first position and from a second outlet orifice in a second position.

33. (Previously presented) The beverage selection manifold of claim 32 wherein the body further comprises a portion that extends past an outer edge of the

manifold body, such that the portion can be grasped by a user for positioning the detachable body in the first position or the second position.

34. (Previously presented) The beverage selection manifold of claim 32 wherein the first and second inlet orifices are configured for flow of carbonated and non-carbonated water, respectively, and wherein the body enables a selection of either carbonated water or non-carbonated water for each of first and second outlet orifices.

35. (Cancelled)

36. (Previously presented) The beverage selection manifold of claim 32 wherein the at least one body comprises a cap configured to be removed and including a channel therein, the cap positionable adjacent an outer wall of one of the cells in a first cap position and a second cap position, wherein the channel allows fluid communication between one of the first or second outlet openings and the first inlet fluid path in the first position and between one of the first or second outlet openings and the second inlet fluid path in the second position.

37. (Cancelled)

38. (Original) A method of switching a supply line to a mixing and dispensing valve comprising:

a) providing a plurality of mixing and dispensing valves in fluid communication with a manifold block, the manifold block having a carbonated water channel and a noncarbonated water channel therethrough and a plurality of paired first and second outlet openings, each pair associated with one of the mixing and dispensing valves;

b) providing a removable selector for each of the plurality of mixing and dispensing valves;

c) connecting one of the removable selectors to one of a carbonated water supply or a non-carbonated water supply to a selected one of the plurality of mixing and dispensing valves by positioning a first removable selector in a first position in which the removable selector closes the first paired outlet opening, while allowing

carbonated water or non-carbonated water to flow through the second paired outlet opening; and thereafter

d) switching the first removable selector body to select the other of a carbonated water supply or a non-carbonated water supply to the selected one of the plurality of mixing and dispensing valves by positioning the first removable selector body in a second position in which the first removable selector body closes the second paired outlet opening, while allowing carbonated water or noncarbonated water to flow through the first paired outlet opening.

39. (Original) The method of claim 38 wherein positioning the first removable selector body in a first position comprises:

a) grasping a portion of the first removable selector body that extends past an outer edge of the manifold block and removing the first removable selector body from the manifold block; and

b) returning the first removable selector body to the manifold block in the second position.

40. (Original) The method of claim 38 further comprising positioning a retaining device against the manifold block to hold the first removable selector body in place.

41. (Original) A method of setting up a beverage dispenser comprising:

a) providing the beverage dispenser with a beverage selection manifold comprising:

i) a manifold block having first and second inlet channels therethrough and at least five paired first and second outlet openings therein; and

ii) a removable selector body associated with each paired first and second outlet opening;

b) positioning one of the removable selector bodies in a first position in which carbonated water entering the manifold block through the first inlet channel passes through the first paired outlet opening and noncarbonated water from the second inlet channel is prevented from passing through the second outlet opening; and

c) positioning another of the removable selector bodies in a second position in which noncarbonated water entering the manifold block through the second inlet channel passes through the second paired outlet opening and carbonated water from the first inlet channel is prevented from passing through the first paired outlet opening.

42. (Original) The method of claim 41 further comprising attaching a retaining device to the manifold block to prevent unintentional change of one or more of the removable selector bodies between the first position and the second position.

43. (Previously presented) A beverage selection manifold for controlling fluid flow therein of carbonated and non-carbonated water for mixing with a syrup to form a beverage, the manifold comprising:

- a) a manifold body including multiple cells, each cell having first and second inlet orifices and first and second outlet orifices,
wherein the first and second inlet orifices are connected to respective first and second elongated channels positioned in the manifold body; and
- b) at least one body configured to be detached from the manifold,
wherein the at least one body is further configured to stop fluid flow from a first outlet orifice in a first position and from a second outlet orifice in a second position; and
- (c) a retaining device to prevent unintentional change of the at least one body between the first and second position.

44. (Cancelled)

45. (Previously Presented) The beverage selection manifold of claim 43 wherein the first and second inlet orifices are configured for flow of carbonated and non-carbonated water, respectively, and wherein the detachable body enables a selection of either carbonated water or non-carbonated water for each of the first and second outlet orifices.

46. (Original) The beverage selection manifold of claim 43 wherein the first and second elongated channels comprise independent channels in the manifold body,

each elongated channel having an opening at an end surface of the manifold body, and wherein the openings are adjacent to one another at the end surface.

47. (Original) The beverage selection manifold of claim 43 wherein the at least one detachable body comprises a body having a fluid channel therethrough.

48. (Original) The beverage selection manifold of claim 43 wherein the manifold body comprises a thermoplastic material.

49. (Cancelled)

50. (Original) The beverage selection manifold of claim 43 wherein the at least one detachable body comprises a removable cap including a channel therein, the cap positionable adjacent one of the cells in a first cap position and a second cap position, wherein the channel allows fluid communication between one of the first or second outlet orifices and the first inlet orifice in the first position and between one of the first or second outlet orifices and the second inlet orifice in the second position.

51. (Previously presented) A beverage selection manifold for controlling fluid flow therein of carbonated and non-carbonated water for mixing with a syrup to form a beverage, the manifold comprising:

- a) a rectangular manifold body including multiple cells, each cell having first and second inlet orifices and first and second outlet orifices, wherein the first and second inlet orifices are connected to respective first and second elongated channels positioned in the rectangular manifold body; and
- b) at least one body configured to be detached from the manifold, wherein the body is further configured to stop fluid flow from a first outlet orifice in a first position and from a second outlet orifice in a second position, and wherein the at least one body further comprises a portion that extends past an outer edge of the rectangular manifold body, such that the portion can be grasped by a user for positioning the at least one detachable body in the first position or the second position.

52. (Original) The beverage selection manifold of claim 51 wherein the at least one body comprises a cap configured to be removed from the manifold and including a channel therein, the cap positionable adjacent one of the cells in a first cap position and a second cap position, wherein the channel allows fluid communication between one of the first or second outlet orifices and the first inlet orifice in the first position and between one of the first or second outlet orifices and the second inlet orifice in the second position.